

Calibrating Agilent PLgel 3 μm 100 \AA Columns with Polystyrene Standards for GPC

Technical Overview

Introduction

Agilent PLgel 3 μm 100 \AA columns are designed specifically for the analysis of low molecular weight discrete molecules in organic solvents. Molecular weight information of a sample is calculated by reference to a standard calibration curve generated by analyzing a series of narrow distribution polymers of known molecular weight. One of the most widely used combinations of calibrant and eluent uses polystyrene narrow standards in tetrahydrofuran. This example shows typical calibration data for Agilent PLgel 3 μm 100 \AA columns using this system. The polystyrene narrow standards in the calibration are Mp 30,300, 5,000, 2,450, 1,270, 580, and 162, which are available as part of the polystyrene calibration kit Agilent S-L-10.

Conditions

Calibrants	Agilent S-L-10 polystyrene narrow standards (p/n PL2010-0101)
Columns	2 \times Agilent PLgel 3 μm 100 \AA , 300 \times 7.5 mm (p/n PL1110-6320)
Concentration	0.1% (w/v)
Eluent	THF
Flow rate	1.0 mL/min
Injection volume	20 μL
Detector	RI
System	Agilent PL-GPC 50



Agilent Technologies

Figure 1 shows overlaid chromatograms of a series of narrowly dispersed polystyrene standards obtained in THF. The lower molecular weight polystyrene 580 has been resolved into individual oligomers by the high efficiency Agilent PLgel 3 μm 100 \AA columns.

Figure 2 shows the resulting calibration curve for the Agilent PLgel 3 μm 100 \AA columns. The calibration is linear up to the exclusion limit of the column (4,000 g/mol).

Agilent PLgel 3 μm Columns

Agilent PLgel individual pore size columns offer high resolution over a specific molecular weight range. The linear portion of the calibration curve, where the slope is at its shallowest, defines the molecular weight region over which optimum resolution is achieved. The Agilent PLgel 3 μm 100 \AA column is ideal for high resolution GPC separations of low molecular weight compounds. Column efficiency increases as the particle size of the packing is reduced. The resolution of individual species is dramatically improved for low MW separations. For these columns, the effective molecular weight range extends to 4,000, with a guaranteed efficiency greater than 100,000 plates per meter.

GPC/SEC Columns and Calibrants from Agilent

Agilent offers a comprehensive portfolio of GPC/SEC columns and calibrants for high-performance separations based on molecular size in solution. Agilent delivers leading solutions for characterizing and separating polymers by GPC/SEC, and manufactures all components for accurate polymer analysis.

Look at the Agilent Literature Library on www.agilent.com/chem/gpc-sec for a comprehensive range of application notes and technical overviews to get the best from your Agilent GPC/SEC columns and instruments.




Figure 1. Overlaid chromatograms of narrow dispersity polystyrene standards. The lower molecular weight polystyrene 580 is resolved into individual oligomers by an Agilent PLgel 3 μm 100 \AA two-column set.




Figure 2. The Agilent PLgel 3 μm 100 \AA calibration curve, linear up to the 4,000 g/mol exclusion limit of the column.

www.agilent.com/chem

Agilent shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Information, descriptions, and specifications in this publication are subject to change without notice.

© Agilent Technologies, Inc., 2015
Printed in the USA
April 30, 2015
5990-8330EN



Agilent Technologies