

Non-refillable cylinders

The recycler



The Air Products recycler tool allows used non-refillable cylinders to be punctured and safely recycled. In the European Union, punctured non-refillable cylinders can be recycled through the normal waste stream as non-hazardous. Outside of the European Union, the relevant local authority should be consulted.

User information

Air Products offer a free recycling service in the European Union, the customer is responsible for all carriage costs and arrangements. Once punctured, non-refillable cylinders no longer need to be transported as dangerous goods, so reducing transport costs.

tell me more

For further advice please contact
Air Products on 01905 758200
and ask for Special Gases & Mixtures,
or email oneuse@airproducts.com

Air Products PLC
2 Millennium Gate, Westmere Drive
Crewe CW1 6AP
T 0800 389 0202
E apukinfo@airproducts.com

Air Products Ireland Ltd.
Unit 950, Western Industrial Estate
Killeen Road, Dublin 12
T 1800 99 50 29
E ieinfo@airproducts.com

www.airproducts.com/oneuse
www.airproducts.co.uk/oneuse
www.airproducts.ie/oneuse

Instructions and Safety Precautions

1. **It is not recommended that toxic or flammable gas cylinders are punctured. These should be returned to Air Products for safe recycling.**
2. Safety glasses should be worn at all times when using the recycler.
3. Prior to puncturing, the cylinder must be completely empty. It is recommended that EIGA IGC document 30 Disposal of Gases is followed before puncturing. This is available as a free download from www.eiga.org.
4. The operator should be familiar with the properties of the gas as described on the safety data sheet, paying particular attention to safety and environmental data.
5. The tool should be fixed to a stable surface using two M6 bolts (not supplied).
6. Place the empty cylinder centrally in the recycler tool and wind the handle slowly clockwise until the cylinder is fully pierced. As a precautionary measure it is advisable to carry this out in well ventilated area such as a fume cupboard or outdoors.
7. The handle should now be wound slowly anti-clockwise to release the cylinder from the tool. The cylinder can then be recycled or disposed of by the preferred method.