

Agilent 7650A Automatic Liquid Sampler (ALS)



Agilent 7650A
ALS



Agilent 7650A ALS
on Agilent 8860 GC



Agilent 7650A ALS
on Agilent 8890 GC



Agilent 7650A ALS
on Agilent Intuvo
9000 GC

The Agilent 7650A automatic liquid sampler (ALS) offers the latest in robust, dependable sampling technology to keep your lab operating with maximum productivity. The 7650A ALS holds fifty 2-mL vials and is compatible with Agilent 8890, 8860, Intuvo, 7890, and 7820 GCs. This injector is an ideal solution for labs with intermediate sampling needs. It also has a capacity of four 4-mL solvent vials and four 4-mL waste vials—for longer unattended analysis.

The Agilent 7650A sampling technology includes 100-millisecond injection, which eliminates a major source of needle discrimination and sample decomposition. Programmable injection means plunger speed can be precisely regulated, enabling optimization for large volume injections or challenging applications. Syringes as small as 1 μL and as large as 500 μL can be used to provide the greatest flexibility for your lab's needs.

The 7650A ALS is a state-of-the-art sample handling injection system that provides the highest levels of precision and reliability for gas chromatographic sampling.

The 7650A ALS consists of:

- Injection tower with 50 vial capacity turret
- Optional large volume syringe carriage

Hardware compatibility

- Agilent 8890, 8860, Intuvo, and 7890 gas chromatographs
- Agilent 7820 gas chromatograph (requires ALS interface card)
- Not interchangeable with Agilent 7693A automatic liquid sampler (ALS) tray
- One 7650A ALS operable on a compatible GC at a time, in front or back inlet
- When used on an Agilent 8890 or 7890 GC, the 7650A ALS may be operated on the front injection port with a 16 vial 7693A ALS injector operated on the back.

Specifications

Chromatographic performance¹

- Sample discrimination $\leq 10\%^2$
- Area reproducibility better than 0.3% RSD³
- Injection linearity less than 5% RSD⁴
- Carryover less than 1 part in 100,000⁵

Injection features

- Standard and on-column injection modes
- Fully programmable dispense rate, draw rate, and injection rate
- Fast injections are performed in less than 100 ms
- Support of 250- and 500- μL syringes with optional large volume syringe carriage
- User-definable sandwich injection mode (two and three layer sandwich injection mode)
- Sensors to detect the presence of the large volume syringe carriage
- A sensor detects the injection port location
- Illuminated syringe for easy viewing
- User-changeable syringe carriage
- Self-aligning injector
- Available solvent-saving mode extends solvent capacity up to eightfold

Sample injection

The 7650A ALS injector provides a wide range of injection capabilities to provide maximum flexibility:

Injection parameter control parameter range

- Variable sampling depth -2 to $+30$ mm above default
- Pre- and postinjection syringe 0–15 rinses for each of solvent A and B
- Sample prewashes 0–15 prewashes
- Viscosity delay 0–7 seconds
- Pre-injection sample pumps 0–15 pumps
- Minimum sample injection 10 nL (with 1 μL syringe)
- Maximum sample injection 50 μL (with 100 μL syringe in standard tower), 250 μL (with 500 μL syringe and large volume syringe carriage)
- Injection plunger speed fast/slow/variable
- Multiple injection mode 1–99 injections of specified volume (COC, PTV, MMI, PP, S/SL) 8890 or 7890 GCs; (PP, S/SL) on 8860 or 7820 GCs
- Injection delay time 0–1 minute (within multiple injection mode)
- Pre-injection dwell time 0–1 minute
- Postinjection dwell time 0–1 minute
- Solvent saver set at 10, 20, 30, 40, and 80% of syringe volume
- Injection range 1 to 50% of syringe volume in increments of 1%
- Syringe size 1, 2, 5, 10, 25, 50, and 100 μL maximum volume with standard syringe carriage
- 250 and 500 μL maximum volume with optional large volume syringe carriage

Sample management

Vial handling

- System supports standard 2 mL vials and micro vial inserts
- 50 sample maximum capacity

Solvent

- 4 mL solvent vials
- 4 × 4 mL (usable solvent capacity of 4 mL per row, 8 mL total)

Syringe support

- Up to 100 µL syringe with standard syringe carriage
- 250/500 µL syringe with optional large volume syringe carriage
- Supports compatible liquid and gastight syringes

Sample sequencing

- Advanced sequencing with random access using Agilent software
- Browser interface sequencing for use with 8860, 8890, and Intuvo
- Simple sequencing using the 7890 Series GCs keyboard
- Simple sequencing using the 7820 GC virtual keyboard
- Next sample overlap
- Capability to run priority samples using software control or GC keyboard (virtual keyboard on 7820 GC)

Physical specifications

Nominal weights and dimensions

Weight

7650A ALS injector—4.5 kg

Height

7650A Injector – 51.5 cm

Above bench surface of top of a 7650A ALS injector as mounted on a 7890 GC: 94 cm

Above bench surface of top of a 7650A ALS injector as mounted on a 7820 GC: 95 cm

Above bench surface of top of 7650A ALS injector as mounted on an Intuvo GC: 102 cm

Above bench surface of top of 7650A ALS injector as mounted on a 8890 GC or 8860 GC: 100 cm

Width (rear mounted)

7650A ALS injector – 21.7 cm

Extension of the 7650A ALS injector past left side of a 7890 or 8890 GC: 83 mm

Extension of the 7650A ALS injector past left side of a 7820 or 8860 GC: 85 mm

Width (on Intuvo)

Extension of the 7650A ALS injector past the left side of an Intuvo GC: 30 mm

Depth (front mounted)

7650A ALS injector – 23.5 cm

Extension of the 7650A injector past front of a 7890 or 8890 GC: 51 mm

Extension of the 7650A injector past front of a 7820 or 8860 GC: 79 mm

Extension of 7650A injector past front of an Intuvo GC: 90 mm

Technical and environmental

- Indoor use only
- Altitude up to 4,300 m
- Ambient operating temperature 15 to 35 °C
- Ambient operating humidity 5 to 95% (noncondensing)
- Pollution degree 2, Installation Cat II

Safety and support

- The injector will not operate if it is not properly mounted on a GC, if the turret is not installed, or if the door is open
- Error indicators
- Flash memory allows product firmware enhancements to be uploaded through a PC
- Onsite repair is available for the 7650A ALS injector
- In the event of any instrument failures, the Agilent industry-leading *Express Exchange* service can minimize downtime by shipping replacement sampler modules within hours
- Contact sales representative to verify compatibility with software
- Not available in all countries

¹ Specifications generated on an Agilent 7890 GC

² From cool on-column analysis of C10–C42; meets or exceeds ASTM 2887

³ Chromatographic conditions for C10–C16

1 μ L injection (5 μ L syringe)

10 injections

1 sample wash; 6 sample pumps

Inlet Split 100:1 (He); 250 °C; 3 mL/min (constant flow)

Column Agilent J&W HP-5MS –
30 m \times 320 μ m, 0.250 μ m df

Oven 180 °C isothermal

Detector FID

⁴ Chromatographic conditions for C14–C16

10 μ L syringe

10 injections for each volume; injection volumes from 10 to 50%

2 sample washes; 6 sample pumps

3 solvent A and B washes postinjection

Inlet Split 25:1 (He); 250 °C; 3.2 mL/min (constant flow)

Column Agilent J&W HP-5MS –
30 m \times 320 μ m, 0.500 μ m df

Oven 100 °C (1 min); 30 °C/min to 250 °C

Detector FID

⁵ Determined by residual analyte area measured in subsequent solvent blank (four solvent A and four solvent B postwashes)

www.agilent.com/chem

This information is subject to change without notice.

© Agilent Technologies, Inc. 2019
Printed in the USA, February 1, 2019
5991-0150EN